



KENFLEX 360 is a high performance, fully flexible homogeneous multi-purpose floor covering and features a non-directional polychrome design incorporating coloured chips to ensure an even colour throughout the thickness. A pallet of six contemporary colours allows for creativity and freedom of design.

KENFLEX360 PROFILE



1. PUR Surface Protection Layer
2. Homogeneous Monolayer
 - pressed and calendered
 - non-directional design

Technical Specifications

	Value	Standard
Classification		
Commercial	31	EN 685
Width	2.0M	EN 426
Roll length	20M	EN 426
Overall thickness	2.0mm	EN 428
Total mass	2,980 g/m ²	EN 430
Residual indentation	~0.04mm	EN 433
Dimensional stability	≤0.40%	EN 434
Colourfastness to light	≥6 degrees	EN ISO 20105 - B02
Slipresistance		
Oil -wet ramp	R10	AS/NZS 4586:2013 App D
Wet pendulum	P4	AS/NZS 4586:2013 App A
Reaction to fire		
Critical radiant flux	8.7 kW/m ²	ASISO 9239.1
Smoke value	117 %.min	ASISO 9239.1
Recommended adhesive		Kenbrock HardGrip or EvaGrip (for wet areas use Roberts 555 PU)
Static electrical propensity	≤2.0kV	EN 1815
Performances		
Abrasion group	T	EN649
Abrasion resistance	≤2.0mm ³	EN660.2
Castor Wheel Test	Suitable	EN425
Chemical resistance	Very Good	EN423
Flexibility	Excellent	EN435
Anti-microbial treatment	Excellent	EN435
Surface Treatment	PUR Protection	

Applications

- Community Housing
- Child Care facilities
- Aged care facilities
- Hospitality
- Educational Facilities
- Offices
- Retail outlets

Sustainability

KENFLEX 360 is 100% recyclable and has very low VOC emissions. This product is manufactured in an ISO 9001 and ISO 14001 certified facility, making it an excellent choice for the environment

Features

- Great flexibility simplifies the installation of bend-up skirting as well as angles and heat welding procedures.
- Abrasion Group T provides excellent resistance to wear and tear in high traffic areas.
- Densely compacted surface for improved wear and ease of maintenance.
- PUR Surface protective treatment for improved resistance to scratching and scuffing.
- Excellent cleaning characteristics, no wax is needed after installation.
- Resistant to the main chemical products used in health care.
- Anti-bacterial and fungicidal properties.
- Anti-static properties (<2kV).
- 10 year commercial warranty.