

Technical Specifications

	Value	Standard
Classification		
Commercial	31	EN 685
Width	2.0M	EN 426
Roll length	20M	EN 426
Overall thickness	2.0mm	EN 428
Wear layer thickness	0.50mm	EN 429
Total mass	2,865g/m ²	EN 430
Residual indentation	0.04mm	EN 433
Dimensional stability	-0.05%	EN 434
Colourfastness to light	6-7	EN ISO 20105-B02
Slip resistance		
Oil-wet ramp	R10	AS/NZS 4586
Wet pendulum	Y	AS/NZS 4586
Reaction to fire		
Critical radiant flux	8.7kw/m ²	ASISO 9239.1
Smoke value	109%	ASISO 9239.1
Fungal resistance	0 growth rate	EN ISO 846
Static electrical propensity	<2.0kv	EN 1815
Chemical resistance	Pass	EN 1815
Recommended adhesive		Kenbrock HardGrip or EvaGrip

Applications

- Community housing and facilities
- Offices and showrooms
- Educational facilities
- Aged care facilities
- Retail fitouts

Sustainability

- Supreme is made with 32% post consumer recycled content.

Features

- 0.50mm wear layer
- Easy Clean UV™ PUR surface treatment for ease of maintenance
- R10 slip resistance
- Functional for multi-purpose applications
- 7 Year commercial warranty
- Glass Fibre reinforced for improved dimensional stability

Profile

