

Gate 5, 2 Normanby Road Clayton VIC 3168, Australia Telephone: 61 3 9545 2777 Web: http://www.csiro.au

Registered Testing Authority - CSIRO

19 June 2018

Our Ref. EN13 / 2556 03/0212

TEST REPORT No. 8103.1

Requested by:	Kenbrock Pty Ltd 22-24 Edson Road Dandenong South Vic 3175
on (date): Manufacturer:	4 May 2018 Kenbrock
Product Desc.:	Cushion Stone, Vinyl Tiles, PU Top Coa
Sampling details:	
Where:	At customer premises
Date:	7 May 2018
By whom:	customer (delivered by courier)

How (methods): N/A

The results reported relate only to the sample(s) tested and the information received. No responsibility is taken for the accuracy of the sampling unless it is done under our own supervision. CSIRO cannot accept responsibility for deviations in the manufactured quality and performance of the product. While CSIRO takes care in preparing the reports it provides to clients, it does not warrant that the information in this particular report will be free of errors or omissions or that it will be suitable for the client's purposes. CSIRO will not be responsible for the results of any actions taken by the client or any other person on the basis of the information contained in the report or any opinions expressed in it. The reproduction of this test report is only authorised in the form of a complete photographic facsimile. Our written approval is necessary for any partial reproduction.

This test report consists of 5 pages

	SUMMARY OF SLIP RESISTANCE TESTS PERFORMED:		
		Result	Class
AS 4586:2013	Slip resistance classification of new pedestrian surface materials		
	Appendix A: WET PENDULUM TEST METHOD (Slider 96):		
	Mean SRV:	39	P3
AS 4586:2013	Slip resistance classification of new pedestrian surface materials,		
(Amendment No. 1)	Appendix D: OIL-WET INCLINING PLATFORM TEST METHOD		
	Corrected mean overall acceptance angle:	19°	R 11

In order to interpret the classifications, please refer to Standards Australia Handbook 198, An Introductory Guide to the Slip Resistance of Pedestrian Surface Materials, which recommends minimum classifications for a wide variety of locations.

It is important to realise that test results obtained on unused factory-fresh samples may not be directly applicable in service, where proprietary surface coatings, contamination, wear and subsequent cleaning all influence the behaviour of the pedestrian surface.



Gate 5, 2 Normanby Road Clayton VIC 3168, Australia Telephone: 61 3 9545 2777 Web: http://www.csiro.au

REPORT NO:8103.1ISSUE DATE:19 June 2018MANUFACTURER:KenbrockPRODUCT DESC:Cushion Stone, Vinyl Tiles, PU Top Coat

Page 2 of 5

PHOTOS:



Top view





Gate 5, 2 Normanby Road Clayton VIC 3168, Australia Telephone: 61 3 9545 2777 Web: http://www.csiro.au

REPORT NO:8103.1ISSUE DATE:19 June 2018MANUFACTURER:KenbrockPRODUCT DESC:Cushion Stone, Vinyl Tiles, PU Top Coat

Page 3 of 5

SLIP RESISTANCE CLASSIFICATION OF NEW PEDESTRIAN SURFACE MATERIALS

WET PENDULUM TEST METHOD

	RIED OUT IN / 013 (Appendix /		ICE WITH			Test Date:	6 June 2018	
710 4000.21						Test Date.		
RESULTS: Location:		Slip Resistance Laboratory			Co	Slider used: 96 Conditioned with grade P400 paper, dry and Imperial Lapping Film Grade 3MIC, wet		
	Sample: Cleaning: Temperature:	Unfixed Deionized water 22.1°C						
	Friction Tester: cted by: Khanh		001 (S/N: 0)312, calibra	ated 16/06/	2016)		
		Specimer 1	1 2	3	4	5		
Last 3 swings (BPN)		41 40	39 38	40 39	43 42	39 38		
		40	38	38	42	38		
Average	es	40	38	39	42	38		
					Mea	an SRV :	39	
					CL	ASS :	P3	



Gate 5, 2 Normanby Road Clayton VIC 3168, Australia Telephone: 61 3 9545 2777 Web: http://www.csiro.au

REPORT NO:8103.1ISSUE DATE:19 June 2018MANUFACTURER:KenbrockPRODUCT DESC:Cushion Stone, Vinyl Tiles, PU Top Coat

Page 4 of 5

SLIP RESISTANCE CLASSIFICATION OF NEW PEDESTRIAN SURFACE MATERIALS

OIL-WET INCLINING PLATFORM TEST METHOD

-	ED OUT IN ACCO 3 (Appendix D) (A	-		Test Date: 6 June	2018
Location:	Slip Resistance L	aboratory	Test conducted by: I	KH, AG	
Sample Unfix	ed				
Joint width: 0) mm				
Surface struc	ture:	[] Smooth [X] Profiled [] Structure	ed		
RESULTS					
Corrected n	nean overall ac	ceptance angle	e: 19 °		
Displaceme	ent space:		ot tested		
CLASSIFI	CATION:	Slip Resista	nce Assessmen	t Group:	R 11
		Displaceme	nt Space Asses	sment Group:	-

Test shoe used: Leipzig V73-SP



Gate 5, 2 Normanby Road Clayton VIC 3168, Australia Telephone: 61 3 9545 2777 Web: http://www.csiro.au

REPORT NO: ISSUE DATE: MANUFACTURER: PRODUCT DESC:

8103.1 19 June 2018 Kenbrock Cushion Stone, Vinyl Tiles, PU Top Coat Page 5 of 5

Date and Place

19 June 2018,

Clayton, Vic

Name, Title and Digital Signature:

KHANH HO Technical Officer Tel: 61 3 95452777 Email: Khanh.Ho@csiro.au