


Profile



1. Dura Coat Surface Protection
2. 0.3mm Wear Layer
3. Decor Layer
4. Recycled Vinyl
5. Fibreglass Core
6. Recycled Vinyl
7. LLT-R Rubber Backing

Technical Specifications

Physical Properties

Wear layer	0.30mm
Thickness	5.0mm
Size	177.8mm x 1219.2mm
Qty per carton	10
M ² per carton	2.17m ²
Dura Coat surface treatment	Yes
Underfloor heating	Suitable

Test Results

Test	Standard	Result	
Classification	Heavy Domestic - Light Commercial	EN685	34
Residual indentation	EN433	<0.1mm	
Dimensional stability	EN434	≤ 0.25%	
Colourfastness to Light	ISO105-B02	6	
Abrasion Resistance	EN428	P	
Slip resistance	Oil wet ramp	AS/NZS4586	R10
	Wet pendulum	AS/NZS4586	tba
Reaction to fire	Critical radiant flux	AS/ISO9239-1	8.8kw/M ²
	Smoke value	AS/ISO9239-1	604.9%
Impact sound Reduction	ISO717-2	9dB	
Recommended adhesive	Kenbrock Smart Grip 8012		

Applications

- Domestic
- Commercial
- Retail
- Apartments
- Aged Care
- Receptions
- Offices

Sustainability

FastFIT makes environmental sense. It contains at least 25% recycled content, it is low VOC and has no heavy metal substances.

FastFIT is manufactured in an ISO9001 and ISO14001 facility.

Features

- 5.0mm plank thickness for superior foot comfort and enhanced acoustic properties
- 0.3mm PU wear layer and Dura Coat surface protection for easy maintenance
- Convenient modular 'drop down' floor laying
- Highly stable fibreglass core layer
- 15 year domestic warranty
- 3 year commercial warranty