

# KENECT

## ADVANCED HYBRID FLOORING



Kenbrock

### KENECT

Carpet Courts Kenect range of hybrid planks is a multi-layered, waterproof floor which combines the most advanced hybrid core technology with the best features of LVT. The core of Kenect is constructed using limestone calcium bonded with polyvinyl chloride (PVC). This ensures the product is both dimensionally and structurally stable. Planks consist of 6.5mm thickness and a 0.55mm wear layer in a 228.6 x 1524mm format.

	KENECT		
<b>DESCRIPTION</b>			
Total thickness	EN 428	mm	6.5
Wearlayer thickness	EN 429	mm	0.55
Weight	EN 430	g/m <sup>2</sup>	9020
Dimensions	EN 426	mm	228.6 x 1524
<b>CLASSIFICATION</b>			
Norm / Product specification	-	-	EN 653
European classification	EN 685	class	33-42
Fire rating	AS ISO 9239-1	kW/m <sup>2</sup>	8.0
		smoke%/min	105
Slip resistance	AS 4586	class	R10
	AS 4586:2013	class	P2
<b>PERFORMANCES</b>			
Wear group	EN 660/1	-	T
Dimensional stability	EN 434	%	0.20
Residual indentation	EN 433	mm	0.05
Colour fastness	EN 20 105-B02	degree	≥ 6
Impact sound insulation	EN ISO 717-2	dB	20
Impact sound insulation	AS ISO 717.2-2004	LnTw ≤	58
Surface treatment	-	-	PUR+ Matt
VOC	ASTM D5116	mg/m <sup>2</sup> /hr	0.035
Guarantee Residential	-	years	Lifetime
Guarantee Commercial	-	years	15
<b>CE</b>	EN 14041		